

XEF 125 PERFORMANCE



BLACK VERSION



WHITE VERSION

ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
MAXIMUM POWER	11 kW (15 PS) to 9.750 rpm
MAXIMUM TORQUE	11,8 Nm to 6.750 rpm
DISPLACEMENT	124,66 cc
BORE	52 mm
STROKE	58,7 mm
DISTRIBUTION	SOHC 4-valve, Variable camshaft timing
IGNITION	Electronic
STARTER	Electric
GEARS	6
CLUTCH	Wet multidisc, back-torque limiter
EXHAUST	Manifold and muffler Euro5 by ARROW
FRAME	Perimeter frame steel CrMo
SUB FRAME	Removable in steel
SWINGARM	Steel, progressive link
TIRES	90/90x21 - 120/90x18
WHEELS	Aluminium, black anodized
BRAKES	Disc "Wave" ø260mm - Disc "Wave" ø220mm, combined brake system
TRIPLE CLAMPS	Forged aluminum
FRONT SUSPENSION	FANTIC ø41mm USD
REAR SUSPENSION	FANTIC 125 - preload regulation
HANDLEBAR	ø22 steel
LIGHTS	Full LED rear, Halogen front
LENGTH	2110mm
SEAT HEIGHT	915mm
WHEELBASE	1420mm
DRY WEIGHT	112 kg
FUEL TANK	capacity 7,5 l
FUEL CONSUMPTION	1,8 l/100 km
CO2 EMISSION	43 g/km

ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
MAXIMUM POWER	11 kW (15 PS) to 9.750 rpm
MAXIMUM TORQUE	11,8 Nm to 6.750 rpm
DISPLACEMENT	124,66 cc
BORE	52 mm
STROKE	58,7 mm
DISTRIBUTION	SOHC 4-valve, Variable camshaft timing
IGNITION	Electronic
STARTER	Electric
GEARS	6
CLUTCH	Wet multidisc, back-torque limiter
EXHAUST	Manifold and muffler Euro5 by ARROW
FRAME	Perimeter frame steel CrMo
SUB FRAME	Removable in steel
SWINGARM	Aluminium, variable section and progressive link
TIRES	90/90x21 - 120/90x18
WHEELS	Aluminium, black anodized
BRAKES	Disc "Wave" ø260mm - Disc "Wave" ø220mm, combined brake system
TRIPLE CLAMPS	Aluminum, CNC racing triple clamps
FRONT SUSPENSION	FANTIC FRS ø41mm USD, racing setup, forged aluminium fork bottoms
REAR SUSPENSION	FANTIC FRS 125 Piggyback - preload and hydraulic regulation
HANDLEBAR	ø28 aluminum
LIGHTS	Full LED front and rear
LENGTH	2110mm
SEAT HEIGHT	915mm
WHEELBASE	1420mm
DRY WEIGHT	108 kg
FUEL TANK	capacity 7,5 l
FUEL CONSUMPTION	1,8 l/100 km
CO2 EMISSION:	43 g/km

XEF 125 COMPETITION



WHITE VERSION



BLACK VERSION