## 50 PERFORMANCE



BLACK VERSION



GINE	Single cylinder 2 stroke, Euro5, liquid cooled
LINDER	48,9 cc
RBURETOR	DellOrto ø16 mm
RE	40,3 mm
ROKE	39 mm
EL INTAKE	Membrane
NITION	Electronic, variable
ARTER	Kick starter
ARS	6
итсн	Multidisc in oil
HAUST	Manifold and muffler Euro5 by BigOne
2 EMISSION	50.32 g/km*
EL CONSUMPTION	2.18 l/100 km*
AME	Perimeter in steel CrMo
B FRAME	Removable in steel
/INGARM	Steel, and progressive link
RES	100/80x17 - 130/70x17
IEELS	Aluminium, anodised black and CNC hubs
AKES	Front disc "Wave" ø260mm - Rear disc "Wave" ø220mm
IPLE CLAMPS	Aluminium
ONT SUSPENSION	FANTIC FRS ø41mm USD
AR SUSPENSION	Mono FANTIC FRS 50
NDLEBAR	Steel, ø22mm
HTS	Full LED rear, Halogen front
NGTH	2040mm
AT HEIGHT	870mm
IEELBASE	1420mm
EIGHT	95 kg
EL TANK	capacity 7,5 l



ENGINE	Single cylinder 2 stroke, Euro5, liquid cooled
CYLINDER	48,9 cc
CARBURETOR	DellOrto ø16 mm
BORE	40,3 mm
STROKE	39 mm
FUEL INTAKE	Membrane
IGNITION	Electronic, variable
STARTER	Kick starter
GEARS	6
CLUTCH	Multidisc in oil
EXHAUST	Manifold and muffler Euro5 by BigOne
CO2 EMISSION	50.32 g/km*
FUEL CONSUMPTION	2.18 l/100 km*
FRAME	Perimeter in steel
SUB FRAME	Removable in steel
SWINGARM	Steel, variable and progressive link
TIRES	100/80x17 - 130/70x17
WHEELS	Aluminium, anodised black and CNC hubs
BRAKES	Front disc "Wave" ø260mm – Rear disc "Wave" ø220mm
TRIPLE CLAMPS	Aluminium, CNC machined
FRONT SUSPENSION	FANTIC FRS ø41mm USD, racing setup
REAR SUSPENSION	Mono FANTIC FRS 50 Piggyback – 2 regulation
HANDLEBAR	Aluminium, ø28mm without cross bar
LIGHTS	Full LED rear, Halogen front
LENGTH	2040mm
SEAT HEIGHT	875mm
WHEELBASE	1420mm
WEIGHT	95 kg
FUEL TANK	capacity 7,5 l

## The second secon



WHITE VERSION

## XIII PERFORMANCE



BLACK VERSION



	WHITE VERSION
GINE	Single cylinder 4 strokes Euro5, liquid cooled
XIMUM POWER	<b>3</b> ,
	11 kW (15 PS) to 9.750 rpm
XIMUM TORQUE	11,8 Nm to 6.750 rpm
PLACEMENT	124,66 cc
RE	52 mm
ROKE	58,7 mm
TRIBUTION	SOHC 4-valve, Variable camshaft timing
ITION	Electronic
ARTER	6
ARS	6
JTCH	Wet multidisc, back-torque limiter
HAUST	Manifold and muffler Euro5 by ARROW
AME	Perimeter frame steel CrMo
B FRAME	Removable in steel
INGARM	Steef, progressive link
ES	100/80x17 - 130/70x17
EELS	Aluminium, black anodized
AKES	Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system
PLE CLAMPS	Forged aluminum
ONT SUSPENSION	FANTIC ø41mm USD
AR SUSPENSION	FANTIC 125– preload regulation
NDLEBAR	ø22 steel
HTS	Full LED rear, Halogen front
IGTH	2110mm
AT HEIGHT	880mm
EELBASE	1435mm
/ WEIGHT	112 kg
EL TANK	capacity 7,5 l
EL CONSUMPTION	1,8 l/100 km
2 EMISSION	43 g/km



ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
MAXIMUM POWER	11 kW (15 PS) to 9.750 rpm
MAXIMUM TORQUE	11,8 Nm a 6.750 rpm
DISPLACEMENT	124,66 cc
BORE	52 mm
STROKE	58,7 mm
DISTRIBUTION	SOHC 4-valve, Variable camshaft timing
IGNITION	Electronic
STARTER	Electric
GEARS	6
CLUTCH	Wet multidisc, back-torque limiter
EXHAUST	Manifold and muffler Euro5 by ARROW
FRAME	Perimeter frame steel CrMo
SUB FRAME	Removable in steel
SWINGARM	steel, progressive link
TIRES	100/80x17 - 130/70x17
WHEELS	Aluminium, black anodized
BRAKES	Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system
TRIPLE CLAMPS	Aluminum, CNC racing triple clamps
FRONT SUSPENSION	FANTIC FRS ø41mm USD, racing setup, forged aluminium fork bottoms
REAR SUSPENSION	FANTIC FRS 125 Piggyback – preload and hydraulic regulation
HANDLEBAR	ø28 in alluminio
LIGHTS	Full LED front and rear
LENGTH	2110mm
SEAT HEIGHT	880mm
WHEELBASE	1435mm
DRY WEIGHT	112 kg
FUEL TANK	capacity 7,5 l
FUEL CONSUMPTION	1,8 l/100 km
EMISSIONI CO2	43 g/km

## XMF125 COMPETITION



WHITE VERSION

16